

ROVER
RL2000



JOIN THE RIDE



ROVER RL2000



JOIN THE RIDE



Front and Rear
Dash Camera



Streamlined
Headlight Design



Front And
Rear Seat Heating



7" TFT
Panel Meter



Gate Belt
Transmission



Six Storage
Space in Total



Front Structure
Design



Streamlined
Design



JBL Audio
System



SONIC BLACK

PHANTOM BLACK

MOONLIT WHITE

STARLIGHT SILVER

Model	ROVER RL2000
Engine	V2 Cylinder, 4-stroke, Air-cooled, OHV, EFI
Displacement (cc)	1,976
Bore x Stroke (mm)	107.95 x 107.95
Maximum Power	74 kW @ 5,000 rpm
Maximum Torque	158 N.m @ 3,000 rpm
Emission Standard	International-IV
Transmission Type / Final Drive	Belt
Clutch Type	Hydraulic, Wet Multi-disc, Sliding Clutch
Compression Ratio	9.75:1
Dimensions (L x W x H) mm	2,600 x 1,010 x 1,380
Wheelbase (mm)	1,640
Net Weight (kg)	440
Seat Height (mm)	700
Full Tank Capacity (L)	18
Chassis	Steel Tube Cradle Frame
Front Brake	Floating Double Disc
Rear Brake	Floating Single Disc
ABS + CBS	Available
TCS Traction Control System	Switchable
Reverse Gear	Available
Front Tyre Type	130/70 R18 Helios
Rear Tyre Type	180/60 R16 Helios
Front Suspension	Vertical Telescopic Cylinder Type
Rear Suspension	Central Monoshock
Rear Fork	Aluminium
Wheel	Aluminium
Gear Shifting Type	6-speed Transmission
Ground Clearance (mm)	130

Distributed by



MFORCE BIKE HOLDINGS SDN. BHD.(751410-H)
1485, Jalan Seruling, Kawasan Perindustrian Valdor, 14200 Sungai Jawi, Pulau Pinang, Malaysia.
Tel: 604-545 2222 | Fax: 604-545 2288 | Email: help@mforce.my



*Specifications and features are subject to change without prior notice.